



QUANTITA' OLIO (LITRI)	HL/300	HL/420
LIVELLO MINIMO	4	5
OLIO UTILE	38	55
OLIO TOTALE	42	60

PESO CENTRALINA SENZA OLIO	HL/300	HL/420
	50	60

MOTORI MONOFASE AIR 230V - 50Hz				
CV	KW	Ø	I _N A	I _A A
1	0.75	19	6	⚠
1.5	1.1	19	7.6	
2	1.5	19	8.95	
2.5	1.8	19	12.8	
3	2.2	19	14.7	

MOTORI TRIFASE AIR 400-415V - 50Hz (230-240V - 50Hz)				
CV	KW	Ø	I _N A	I _A A
1	0.75	19	1.9 (3.3)	⚠
1.5	1.1	19	3 (5.2)	
2	1.5	19	3.6 (6.2)	
3	2.2	19	6.6 (11.4)	

- ⚠ - VARIAZIONE QUOTA RIF. COPERCHIO PER ELETR. BISOLENOIDE (A RICHIESTA)
- ⚠ - CORRENTE DI AVVIAMENTO: $I_A = I_N \times 3$

MOD.	CAPPOTTINA
HL300	SI
HL420	SI
HL300AR	NO
HL420AR	NO

VELOCITA' PISTONE IN SALITA M/SEC (A CARICO MEDIO)	POMPA L/1' (Ø 19)				PISTONE	PRESSIONE STATICA IN BAR																			PORTATA UTILE (P. UTILE+P. CABINA+ARCATATA+ACC. = kg)														
	23	18	12	8		Ød	e	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32		33	34	35	36	37	38	39	40	41	42	43	44	45	46
	0.19	0.15	0.10	0.06		50	5	281	320	359	398	438	477	516	556	595	634	673	713	752	791	830	870	7.5		267	306	345	384	424	463	502	542	581	620	659	699	738	777
0.13	0.10	0.07	0.04	60	5	392	450	505	562	618	675	732	788	845	901	958	1015	1071	1128	1184	1240	7.5	368	425	481	538	594	651	707	764	820	877	933	990	1046	1103	1160	1216	
0.09	0.07	0.05	0.03	70	5	535	612	688	766	843	920	997	1074	1151	1227	1305	1382	1458	1535	1612	1689	7.5	502	579	656	733	810	887	964	1041	1118	1195	1272	1349	1426	1503	1580	1657	
0.07	0.06	0.04	0.02	80	5	704	805	905	1006	1106	1207	1307	1408	1508	1609	1709	1810	1910	2011	2111	2212	7.5	649	749	850	950	1051	1151	1252	1352	1453	1554	1654	1755	1855	1956	2056	2157	
0.06	0.05	0.03	0.02	85	7.5	722	836	949	1063	1176	1290	1403	1517	1630	1744	1857	1971	2084	2198	2311	2425	12	566	667	767	869	968	1069	1169	1270	1370	1471	1571	1672	1772	1873	1973	2074	
0.06	0.05	0.03	0.02	90	5	890	1017	1144	1271	1398	1526	1653	1780	1908	2035	2162	2289	2416	2544	2671	2798	7.5	816	944	1071	1198	1325	1453	1580	1707	1834	1962	2089	2216	2343	2471	2598	2725	
					12	717	844	971	1098	1225	1353	1480	1607	1734	1861	1988	2116	2243	2370	2497	2624																		

Ø STELO	MONOFASE 50Hz 230V ± 5%				TRIFASE 50Hz 230V/400V ± 10%			
	8	12	18	23	8	12	18	23
1 (0.75) Ø19	1 (0.75) Ø19	1.5 (1.1) Ø19	2 (1.5) Ø19	2.5 (1.8) Ø19	1 (0.75) Ø19	1.5 (1.1) Ø19	2 (1.5) Ø19	3 (2.2) Ø19
1.5 (1.1) Ø19	1.5 (1.1) Ø19	2 (1.5) Ø19	2.5 (1.8) Ø19	3 (2.2) Ø19	1 (0.75) Ø19	1.5 (1.1) Ø19	2 (1.5) Ø19	3 (2.2) Ø19
2 (1.5) Ø19	2 (1.5) Ø19	2.5 (1.8) Ø19	3 (2.2) Ø19	3 (2.2) Ø19	1 (0.75) Ø19	1.5 (1.1) Ø19	2 (1.5) Ø19	3 (2.2) Ø19
2.5 (1.8) Ø19	2.5 (1.8) Ø19	3 (2.2) Ø19	3 (2.2) Ø19	3 (2.2) Ø19	1 (0.75) Ø19	1.5 (1.1) Ø19	2 (1.5) Ø19	3 (2.2) Ø19

- IL PESO ESPRESSO IN TABELLA E' STATO CALCOLATO TENENDO GIA' CONTO DEL PESO DELLO STELO PER UNA CORSA MASSIMA (VEDI DIS. 9020/... 9030/...)

UT	TABELLA PER LA RICERCA DEI VALORI DI PRESSIONE - VELOCITA' - POMPA - MOTORE AIR (50Hz) IN RELAZIONE AL Ø STELO E PORTATA SU CENTRALINA - HL -	DATA
		10/18
		DIS. N° 9018/HL-50Hz

